

Mynute HE

High efficiency system boiler

SEDBUK 'A' RATED

ENERGY EFFICIENCY
RECOMMENDED

COMPATIBLE WITH ZENITH
SOLAR THERMAL

COMPATIBLE WITH ENERGY
SAVING CONTROLS



Mynute HE

High efficiency system boiler

SPECIFICATIONS	Mynute 12HE	Mynute 15HE	Mynute 20HE	Mynute 25HE	Mynute 30HE	Mynute 35HE
Central Heating						
Heat input (kW)	12	15	20	25	30	34.6
Maximum heat output (kW) 60/80°C	11.84	14.81	19.68	24.53	29.31	33.67
Maximum heat output (kW) 30/50°C	12.74	15.9	21.16	26.3	31.83	36.54
Weight						
Dry weight (kg)	38	38	38	39	42	42
Dimensions						
Height (mm)	740	740	740	780	780	780
Width (mm)	400	400	400	400	450	450
Depth (mm)	342.5	342.5	342.5	358	358	358
Flue Details (concentric & twin)						
Max horizontal flue length (60/100mm)	7.8m	7.8m	7.8m	7.8m	7.8m	7.8m
Max vertical flue length (60/100mm)	8.8m	8.8m	8.8m	8.8m	8.8m	8.8m
Max horizontal flue length (80/125mm)	20.0m	20.0m	20.0m	20.0m	20.0m	20.0m
Max vertical flue length (80/125mm)	25.0m	25.0m	25.0m	25.0m	25.0m	25.0m
Max horizontal flue length (80mm/80mm)	40m/40m	40m/40m	40m/40m	40m/40m	40m/40m	40m/40m
Max vertical flue length (80mm/80mm)	40m/40m	40m/40m	40m/40m	40m/40m	40m/40m	40m/40m
Flue type approvals	C13 – C23 – C33 – C43 – C53 – C83 – B23					
Efficiency						
SEDBUK (%)	90.7 (A)	90.7 (A)	90.5 (A)	90.4 (A)	90.2 (A)	90.0 (A)
NOx Class	5	5	5	5	5	5

*From casing or 25mm above flue elbow (whichever is applicable)

MYNUTE HE CONTROL PANEL



SEDBUK 'A' rated.

Reduces running costs by up to 35% more than a conventional boiler, helping to safeguard the environment.

Low pressure loss reduces noise and increases pump performance.

Extremely high modulation ratio, increasing efficiency and component longevity.

Low-NOx - highest class-5 performance.

Self-start programming protects the pump from sticking during long periods of inactivity.

Anti-cycling control prevents energy wasteful on/off cycling and reduces wear and tear.

Built-in frost protection, protects the appliance from damage during periods of cold weather.

Versatile horizontal or vertical flueing options – using Vokèra's concentric or twin flue systems – enable the boiler to be sited almost anywhere in the home.

Adding a Vokèra energy saving control to the Vokèra Mynute HE can increase the boilers efficiency by a further 10% so ask your installer about the range of Vokèra energy saving controls.

Integral clock/programmer aperture, enabling direct control over the central heating timings.

Intuitive control panel ensures the appliance is easy to operate and adjust.

Built-in thermo-regulation to increase further fuel efficiency.

Can be converted to LPG with LPG Kit.

Compatible with Zenith Solar thermal.

ENERGY SAVING CONTROLS AND OPTIONS

Description	Code
OpenTherm RF Control*	611
Weather compensation control	2359259
White pipe cover 400mm/450mm	518/519
Digital clock	514

*Contact Vokèra Technical Helpline for advice.

Further information on these controls can be found in the Vokèra Intelligent controls brochure.



Vokèra Ltd Borderlake House, Unit 7 Riverside Industrial Estate, London Colney, AL2 1HG

Email: enquiries@vokera.co.uk Web: www.vokera.co.uk

Vokèra Ireland West Court, Callan, Co Kilkenny

Tel: 0844 391 0999

Tel: 056 7755057

Fax: 0844 391 0998

Fax: 056 7755060

Vokèra Limited reserve the right to change specification without prior notice. Consumers statutory rights are not affected. A Riello Group Company. Company Reg No.: 1047779

Vokèra is a licensed member of the Benchmark scheme which aims to improve the standards of installation and commissioning of domestic hot water systems in the UK.